



- Colour: 超钢
- 单孔安装
- 高仪持久表面
- 35 毫米陶瓷阀芯
- 可拔出式两用型花洒 - 可在正常出水和喷洒模式之间来回切换
- 分水器：起泡器/快速清洁花洒喷嘴
- 自动返回龙头出水
- 可调流量限制器
- 旋转出水
- 旋转角度为140°
- 金属把手
- 止逆阀
- 软管
- 快速安装系统
- 推荐最低水压 1.0 Bar

The diagram is an exploded view of a microscope. It shows the following components and their assembly sequence:

- 1**: A small circular component, likely a lens or filter, shown being inserted into the top of component 2.
- 2**: A cylindrical component that fits into the top of component 3.
- 3**: A larger cylindrical component that fits into the top of component 4.
- 4**: A rectangular component that fits into the top of component 5.
- 5**: A side-mounted component, possibly a camera or light source, shown being attached to the side of the main assembly.
- 6**: A small cylindrical component that fits into the top of component 7.
- 7**: A large cylindrical component that fits into the top of component 8.
- 8**: A component that fits into the top of component 9.
- 9**: The base of the microscope, shown being attached to the bottom of component 10.
- 10**: A cylindrical component that fits into the top of component 11.
- 11**: The bottom-most component, likely a lens or filter, shown being inserted into the bottom of component 10.

The legend box at the bottom right shows details for parts 10 and 11:

10	
11	

\* Optional accessories